




INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶ : A61M 15/00, B05B 11/00		A1	(11) International Publication Number: WO 99/25404
			(43) International Publication Date: 27 May 1999 (27.05.99)
(21) International Application Number: PCT/GB98/03451		(81) Designated States: AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, UA, UG, US, UZ, VN, YU, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).	
(22) International Filing Date: 16 November 1998 (16.11.98)			
(30) Priority Data: 9724223.4 18 November 1997 (18.11.97) GB			
(71) Applicant (for all designated States except US): P A KNOWLEDGE LIMITED [-/-]; Ugland House, P.O. Box 309, George Town, Grand Cayman (KY).			
(72) Inventors; and			
(75) Inventors/Applicants (for US only): POLEY, John [GB/GB]; P.A. Consulting Group, Cambridge Technology Centre, Melbourn, Hertfordshire SG8 6DP (GB). SEENEY, Philip [GB/GB]; P.A. Consulting Group, Cambridge Technology Centre, Melbourn, Hertfordshire SG8 6DP (GB).		Published With international search report. Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.	
(74) Agent: MARKGRAAF PATENTS LIMITED; The Crescent, 54 Blossom Street, York YO24 1AP (GB).			

(54) Title: DRUG DELIVERY DEVICE

(57) Abstract

A drug delivery device for the delivery of a fluid carrying or comprising a therapeutic agent, said device comprising: a reservoir for storing said fluid, and in fluid connection therewith a regulatable pump means for dispensing said fluid via an outlet means; wherein a control means is further provided for selectively controlling the pumping mode of said pump means such that in a first mode said pump means acts to dispense said fluid and in a second mode said pump means acts such that substantially no fluid is dispensed.



FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece			TR	Turkey
BG	Bulgaria	HU	Hungary	ML	Mali	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MN	Mongolia	UA	Ukraine
BR	Brazil	IL	Israel	MR	Mauritania	UG	Uganda
BY	Belarus	IS	Iceland	MW	Malawi	US	United States of America
CA	Canada	IT	Italy	MX	Mexico	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NE	Niger	VN	Viet Nam
CG	Congo	KE	Kenya	NL	Netherlands	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NO	Norway	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	NZ	New Zealand		
CM	Cameroon			PL	Poland		
CN	China	KR	Republic of Korea	PT	Portugal		
CU	Cuba	KZ	Kazakhstan	RO	Romania		
CZ	Czech Republic	LC	Saint Lucia	RU	Russian Federation		
DE	Germany	LI	Liechtenstein	SD	Sudan		
DK	Denmark	LK	Sri Lanka	SE	Sweden		
EE	Estonia	LR	Liberia	SG	Singapore		

DRUG DELIVERY DEVICE

The invention relates to a control means for a drug delivery device and also a drug delivery device including a control means.

A number of therapeutic treatments are administered by inhalation and thus, primarily, are directed to the upper respiratory tract ie the nose and throat.

- 5 Accordingly, a number of conventional devices exist for this purpose. In some instances, for example where a therapeutic agent may be dangerous when a given dose is exceeded, or alternatively, where a therapeutic agent may be potentially addictive, it is important to regulate the administered dose or dose regime. It is therefore important to try and prevent the inadvertent
10 overdosing of a given therapeutic agent or the inadvertent addiction to a given therapeutic agent.

- Conventional dispensers typically include a dispensing means which controls the amount of therapeutic agent delivered per use, or application, of the dispenser. For example, a pump and associated chamber can be used to
15 control the delivery of a selected amount of therapeutic agent, typically in the form of a therapeutic fluid, thus the volume of fluid dispensed is determined by the geometry of the chamber on which the pump acts and therefore for each pumping action a given volume of fluid is dispensed. In this way, provided an individual only uses the dispenser, or pump, a
20 specified number of times over a given period, the dose of therapeutic agent should fall within a dose regime.

However, it is not uncommon for individuals to forget how much of a given quantity of therapeutic agent has been inhaled in any given period and therefore to inadvertently exceed a dosage. Additionally, given that pump
5 operated dispensers sometimes need to be primed for a correct amount of therapeutic agent to be dispensed an individual may not receive a correct dosage of therapeutic agent. And indeed in these circumstances it is possible for an individual to inadvertently exceed his or her recommended dose by following this partial dose, with a full dose and thus run the risk of
10 inadvertent overdose or addiction.

A further complication concerns the fact that increasingly new and effective therapeutic agents are becoming hazardous and therefore if a partial dose, due to inadequate priming, is not taken it is not always advisable to simply dispense into the atmosphere by a technique known as air priming the partial
15 dose. Additionally, it is not always advisable to air prime because of the considerable expense that may be associated with the use of certain therapeutic agents in this way.

It can therefore be seen that there is a need to provide a means for controlling the dispensing of therapeutic agents; and a device including
20 same.

It is therefore an object of the invention to provide a control means in, or for use in, a dispensing device whereby the dose regime of a dispensed therapeutic can be reliably controlled.

According to a first aspect of the invention there is provided a drug delivery device for the delivery of a fluid carrying or comprising a therapeutic agent said device comprising: a reservoir for storing said fluid, and in fluid
5 connection therewith a regulatable pump means for dispensing said fluid via an outlet means; wherein a control means is further provided for selectively controlling the pumping mode of said pump means such that in a first mode said pump means acts to dispense said fluid and in a second mode said pump means acts such that substantially no fluid is dispensed.

- 10 In a preferred embodiment of the invention said reservoir comprises an exit portion comprising a dispensing chamber and associated dispensing channel which is in fluid connection with a storage portion of said reservoir.

In a preferred embodiment of the invention said pump means comprises a
15 selectively controllable bypass valve which has a dual mode of operation. In a first mode when the bypass valve is closed fluid in said reservoir can be dispensed from said device. Alternatively, or additionally, in a second mode when said bypass valve is opened fluid in said reservoir is diverted from an exit portion of said reservoir to a storage portion of said reservoir.

20

More preferably still said bypass valve comprises an aperture covered by a flexibly membrane that allows the passage therethrough or thereby of therapeutic fluid when said bypass valve is in said second mode.

- In yet a further preferred embodiment of the invention said bypass valve
25 comprises an aperture in said dispensing chamber and/or said dispensing channel and a means for releasably sealing same such that when the device is

to dispense a dosage of therapeutic agent said aperture is closed; and when the device is to prevent dispensing of said therapeutic agent the aperture of the bypass valve is opened thus enabling therapeutic agent in said dispensing
5 chamber to be diverted to the storage portion of said reservoir. Ideally, said releasable sealing means comprises an urging means which is ideally controlled using electrical means, and most ideally comprises a solenoid.

It will therefore be apparent that when the urging means acts so as to apply
10 sufficient pressure to the releasable sealing means the aperture in the dispensing chamber is sealed and this ensures that therapeutic agent can be dispensed from the device. Alternatively, when the urging means does not act to apply sufficient pressure to the releasable sealing means the aperture in the dispensing chamber is opened and the therapeutic agent is therefore
15 directed towards the reservoir storage portion.

It therefore follows that the selective control of the urging means status will determine the pumping mode of the pump and so the ability of the delivery device to dispense medication.

In yet a further preferred embodiment of the invention control means ideally
20 in the form of an electronic circuit with at least one microchip is provided so that the number of times the device can dispense a therapeutic agent can be controlled over a set period of time. Additionally, and advantageously, said control means is adapted to record information relating to use of the dispensing device and also to respond to interrogation of same so that, with
25 the provision and use of a suitable display means, an individual can enquire as to how frequently the device may be used over a remaining period of time

or how much medication has already been administered. Additionally further still an interface means is provided whereby data stored on said control means can be down-loaded to another compatible device for further
5 use/analysis. This is useful for determining drug regime compliance either from the perspective of a GP or clinical trials co-ordinator.

An additional advantage intrinsic in the device of the invention concerns an ability to prime the pump means without dispensing the therapeutic agent. As will be well known to those skilled in the art, the loss of prime in pumps
10 is a consequence of fluid leaking out of the relevant chamber, in this instance the dispensing chamber. This typically occurs when the device is jostled or laid on its side. Thus the amount of fluid in the dispensing chamber is decreased and an insufficient dose is administered on use. In order to ensure that a correct dose is administered the conventional device is repeatedly
15 operated, at least once, to refill the dispensing chamber. This involves effecting additional cycles of the device and thus dispensing some therapeutic agent to the atmosphere. However with the device of the invention it is possible to prime the pump with the bypass valve open and thus divert the therapeutic fluid in the dispensing chamber to the reservoir
20 storage portion. In this way, the device can be primed without loss of medication or fluid.

It therefore follows that the control means could be further programmed to enable a user to prime the device each time before usage. For example, it is possible to program the control means so that at least one pump operation is
25 provided, for the purpose of priming with the bypass valve open, and then a further pump operation is provided with the bypass valve closed so as to

ensure that on a selected pump operation the device dispenses a desired amount of therapeutic agent.

- 5 It can therefore be seen that the device of the invention not only enables one to control the number of times a therapeutic agent is dispensed from the device but also it enables repriming without the disadvantages associated with air priming.

- According to a second aspect of the invention there is provided a drug delivery device for the delivery of the fluid carrying or comprising a therapeutic agent. The said device comprising: a reservoir for storing said fluid, and in fluid connection therewith a regulatable pump means for dispensing said fluid via an outlet means; wherein a primer control means is further provided for selectively controlling the pumping mode of said pump means such that in a first mode said pump means acts to dispense said fluid and in a second mode said pump means acts to return fluid to said reservoir.
- 10
15

A single embodiment of the invention will now be described by way of example only. It is notable that this single embodiment is not intended to limit the scope of the application but merely serve for the purpose of comprehension.

- 20 The embodiment of the invention will be described with reference to the single figure which is a part sectional, part peeled-back, perspective view of a device in accordance with the invention. The device comprises a generally cylindrical body member 1 attached to a dispensing nozzle 2 in conventional manner. Nozzle 2 is provided with an actuator member 3 which is adapted

to enable a user to apply pressure thereto using the fingers of one hand. The lower part of body 1 comprises a storage reservoir 4 into which a selected volume of therapeutic fluid can be stored. Centrally located in reservoir 4 there is provided a cylindrical dispensing channel 5 which communicates with, and is in fluid connection with, a dose regulation chamber 6 via a releasable ball closure means 7. Dose regulation chamber 6 is in fluid connection with dispensing channel 8 upon depression of breakback piston 9 as will be described hereinafter. Dispensing channel 8 terminates at the outermost tip of nozzle 2. This arrangement ensures that the fluid stored in reservoir 4 travels through the device to be dispensed via nozzle 2.

Notably, the dimensions of dose regulation chamber 6 and dispensing channel 8 determine the dosage of fluid dispensed upon operation of the device. Thus the dimensions are suitably selected for a given concentration of therapeutic fluid. Or, alternatively, the concentration of a given therapeutic fluid is determined having regard to the dimensions of said dose regulation chamber 6 and channel dispensing means 8.

Actuator 3 is operatively connected to breakback piston 9 in conventional manner such that the depression of actuator 3 results in the downward movement of breakback piston 9. As piston 9 is moved downwardly it travels into the dose regulation chamber 6 and the pressure in same increases until what is known as a break pressure is reached. At this point part of the piston assembly breaks away thus ensuring that the dose regulation chamber 6 is in fluid connection with the dispensing channel 8 and the pressurised fluid then exits the dispensing device.

The exact arrangement for ensuring fluid connection between dose regulation chamber 6 and dispensing channel 8 can be selected from conventional devices, including permutations or variations thereof, and is not intended to limit the scope of the application.

Indeed, the exact arrangement of the pumping mechanism may be selected from conventional devices, including permutations or variations thereof, and is not intended to limit the scope of the application.

- 10 In the device of the invention the dose regulation chamber 6 or, alternatively, the dispensing channel 8 is provided with a bypass valve 10. Bypass valve 10 comprises a cavity provided in the wall of the dose regulation chamber 6 and a releasable closure means in contact therewith. In a preferred embodiment of the invention the releasable enclosure means comprises a
- 15 flexible (or resilient) covering for the aperture, typically in the form of a flexible (or resilient) band which is placed about the outer surface of the dose regulation chamber 6 and also an associated urging means which can be made to selectively press against the releasable band, ideally in the region of the aperture. In the embodiment of the invention shown in the figure the
- 20 releasable urging means comprises a solenoid 11 which can be activated/deactivated, depending on the configuration of the solenoid so as to press against the resilient band. However, in an alternative mode of operation the deactivation/activation of the solenoid will have the opposite effect and the urging member of the solenoid will be positioned remote from
- 25 the resilient band enabling fluid to escape from dose regulation chamber 6 when a given pressure is reached. Clearly the flexibility or resilience of the band is selected with this in mind. In alternative embodiments of the

invention more than one bypass valve may be provided or alternatively at least one bypass valve is provided in either or both the dose regulation chamber 6 or the dispensing channel 8.

- 5 The dispensing device is suitably provided with an electronic circuit means (not shown) which can be programmed to control the operation of said bypass valve in accordance with the dispensing requirements of the device. Additionally, display means (not shown) may be provided so that information stored can be viewed by a user. Additionally, and
- 10 advantageously, the electronics may be programmed for interrogation so that a user may enquire as to the status of the device or the number of doses dispensed over a given period of time and thus the remaining number of doses to be dispensed over a given period of time or indeed any other information that may be beneficial to the successful use of the device.
- 15 Additionally, interface means may be provided so that the device can be used in association with other equipment for the purpose of data analysis.

- Typically therefore, in use, the device is filled with an appropriate amount of selected therapeutic fluid and the electronics is programmed so that, for
- 20 example, the bypass valve is opened for at least one operation of the pump and closed for the next subsequent permitted operation thus ensuring that a full dose of therapeutic fluid is dispensed on the selected operation of the pump. Additionally, a timer may be incorporated into the electronics so that the bypass valve remains open for a predetermined time interval so that in
- 25 this predetermined time interval although the pump may be operated no medication is dispensed. Once a predetermined time interval has elapsed the electronics are programmed so that following priming of the pump on

subsequent operation of the pump a dosage of therapeutic fluid is dispensed if permitted. Thus in this way, at the correct time interval, the user is able to operate the pump at least once in order to prime same and then operate the
5 pump a further time in order to dispense a reliable amount of medication. The aforementioned cycle of the working of the device can be repeated for a given number of times or alternatively, the predetermined time interval may be varied accordingly to a user's requirements so as to provide for a constant and repeatable cycle of medication dispensing or a variable cycle of
10 medication dispensing.

It can therefore be seen that the invention concerns a novel dispensing means for controlling the administration of a therapeutic agent.

CLAIMS

1. A drug delivery device for the delivery of a fluid carrying or
5 comprising a therapeutic agent said device comprising: a reservoir for storing said fluid, and in fluid connection therewith a regulatable pump means for dispensing said fluid via an outlet means; wherein a control means is further provided for selectively controlling the pumping mode of said pump means such that in a first mode said pump means acts to dispense said fluid and in a
10 second mode said pump means acts such that substantially no fluid is dispensed.
2. A drug delivery device according to Claim 1 wherein said reservoir
comprises an exit portion comprising a dispensing chamber and associated
15 dispensing channel which is in fluid connection with a storage portion of said reservoir.
3. A drug delivery device as claimed in either of Claims 1 and 2 wherein
said pump means comprises a selectively controllable bypass valve which has
20 a dual mode of operation.
4. A drug delivery device as claimed in Claim 3 wherein in a first mode
when the bypass valve is closed fluid in said reservoir can be dispensed from
said device.
- 25 5. A drug delivery device as claimed in either of Claims 3 or 4
characterised in that in a second mode when said bypass valve is opened, fluid
in said reservoir is diverted from an exit portion of said reservoir to a storage
portion of said reservoir.
- 30

6. A drug delivery device as claimed in Claim 5 characterised
in that said bypass valve comprises an aperture covered by a flexible
membrane that allows the passage therethrough or thereby of therapeutic fluid
5 when said bypass valve is in said second mode.

7. A drug delivery device as claimed in any of Claims 3 to 6 wherein said
bypass valve comprises an aperture in said dispensing chamber and/or said
dispensing channel and a means for releasably sealing same such that when
10 the device is to dispense a dosage of therapeutic agent said aperture is closed;
and when the device is to prevent dispensing of said therapeutic agent the
aperture of the bypass valve is opened thus enabling therapeutic agent in said
dispensing chamber to be diverted to the storage portion of said reservoir.

8. A drug delivery device as claimed in Claim 7 characterised in that said
15 releasable sealing means comprises an urging means.

9. A drug delivery device as claimed in Claim 8 characterised in that said
urging means is controlled using electrical means and preferably comprises a
20 solenoid.

10. A drug delivery device as claimed in any of Claims 1 to 9 characterised
in that said control means is provided so that the number of times the device
can dispense a therapeutic agent can be controlled over a set period of time.

11. A drug delivery device as claimed in Claim 10 characterised in that said
control means is provided in the form of an electronic circuit with at least one
microchip.

12. A drug delivery device as claimed in any of Claims 1 to 11
characterised in that said control means is adapted to record information
relating to use of the dispensing device and also to respond to interrogation of
5 same.

13. A drug delivery device as claimed in any of Claims 1 to 12
characterised in that an interface means is provided whereby data stored on
said control means can be downloaded to another compatible device for
10 further use/analysis.

14. A drug delivery device as claimed in any of Claims 7 to 13 wherein
said pump is primed in said second mode such that the device can be primed
without loss of medication or fluid.

15
16. A drug delivery device as claimed in any of Claims 3-14 wherein the
control means is adapted to be programmed so that at least one pump action
operation is provided, for the purpose of priming with the bypass valve open,
and then a further pump operation is provided with the bypass valve closed so
20 as to ensure that on a selected pump operation the device dispenses a desired
amount of therapeutic agent.

16. A drug delivery device for the delivery of the fluid carrying or
comprising a therapeutic agent comprising: a reservoir for storing said fluid,
25 and in fluid connection therewith a regulatable pump means for dispensing
said fluid via an outlet means; wherein a primer control means is further
provided for selectively controlling the pumping mode of said pump means
such that in a first mode said pump means acts to dispense said fluid and in a
second mode said pump means acts to return fluid to said reservoir.

14

17. A method of priming a drug delivery device as claimed in any of Claims 5 to 16 in said second mode.

5 18. A drug delivery device substantially as described in the description and/or shown in the figure.

10


15

20

25

30

1 / 1

*Fig. 1*

SUBSTITUTE SHEET (RULE 26)

INTERNATIONAL SEARCH REPORT

International Application No

PCT/GB 98/03451

A. CLASSIFICATION OF SUBJECT MATTER

IPC 6 A61M15/00 B05B11/00

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 6 A61M B05B

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US 5 211 201 A (FAUST VALENTINE ET AL) 18 May 1993	1-5, 15, 16
Y	see abstract; figure 1 ---	10
Y	EP 0 372 863 A (PACESETTER INFUSION LTD) 13 June 1990 see column 10, line 43 - column 11, line 20 ---	10
A	US 5 339 990 A (WILDER ROBERT E) 23 August 1994 see column 7, line 21 - line 48; figures 4A-4C ---	1-5
A	GB 2 083 569 A (AEROSOL INVENTIONS DEV) 24 March 1982 see page 2, line 8 - line 17; claim 1 --- -/--	1-5

☒ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

* Special categories of cited documents

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier document but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

"Z" document member of the same patent family

Date of the actual completion of the international search

27 April 1999

Date of mailing of the international search report

06/05/1999

Name and mailing address of the ISA
European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 apo nl,
Fax: (+31-70) 340-3016

Authorized officer

Villeneuve, J-M

INTERNATIONAL SEARCH REPORT

International Application No
PCT/GB 98/03451

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	US 5 284 133 A (BURNS JAMES S ET AL) 8 February 1994 ----	
A	EP 0 569 611 A (SIEMENS AG) 18 November 1993 -----	

INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/GB 98/03451

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
US 5211201 A	18-05-1993	US 4808161 A	28-02-1989
		US 4826482 A	02-05-1989
		US 4976162 A	11-12-1990
		US 5088515 A	18-02-1992
		US 5116021 A	26-05-1992
		US 4778451 A	18-10-1988
		EP 0621791 A	02-11-1994
		JP 7509144 T	12-10-1995
		WO 9309828 A	27-05-1993
		US 5222946 A	29-06-1993
		US 5364371 A	15-11-1994
		US 5401342 A	28-03-1995
		US 5533389 A	09-07-1996
		US 5526844 A	18-06-1996
		US 5575310 A	19-11-1996
		US 5193990 A	16-03-1993
		US 5178182 A	12-01-1993
		US 5349852 A	27-09-1994
		US 5353837 A	11-10-1994
		US 5195986 A	23-03-1993
		US 5241985 A	07-09-1993
		CA 1290211 A	08-10-1991
		DE 3882966 A	09-09-1993
		DE 3882966 T	25-11-1993
		EP 0332690 A	20-09-1989
		JP 2501198 T	26-04-1990
		WO 8901795 A	09-03-1990
		AT 175270 T	15-01-1999
		CA 2049337 A	02-11-1990
		DE 69032869 D	11-02-1999
		EP 0471000 A	19-02-1992
		JP 5502096 T	15-04-1993
		WO 9013795 A	15-11-1992
		AT 177955 T	15-04-1999
		AU 672154 B	19-09-1996
		AU 1229795 A	11-05-1995
		AU 658825 B	04-05-1995
		AU 7885891 A	10-12-1991
		CA 2082057 A	16-11-1991
		EP 0528947 A	03-03-1993
		FI 925177 A	13-11-1992
		IL 98152 A	30-05-1994
		IL 104253 A	30-03-1995
		IL 107308 A	05-12-1996
		IL 107309 A	04-08-1996
		MX 173229 B	09-02-1994
		WO 9117780 A	28-11-1991
		EP 0558607 A	08-09-1993
		JP 6502789 T	31-03-1994
		WO 9208503 A	29-05-1992
EP 0372863 A	13-06-1990	US 5009641 A	23-04-1991
		CA 2001942 A, C	02-06-1990
		DE 68916196 D	21-07-1994
		DE 68916196 T	19-01-1995
		JP 2264666 A	29-10-1990
US 5339990 A	23-08-1994	NONE	

INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No
PCT/GB 98/03451

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
GB 2083569 A	24-03-1982	FR 2488659 A AU 7385581 A ZA 8105358 A	19-02-1982 18-02-1982 28-07-1982
US 5284133 A	08-02-1994	NONE	
EP 0569611 A	18-11-1993	AT 155715 T DE 59208726 D EP 0739654 A	15-08-1997 28-08-1997 30-10-1996